

The **Drizzle™** series of static spray balls are fixed spray balls offering a good rinse at an economical value. There are no moving parts. These spray balls are suitable for high temperature applications, operations with steam & air. The design is robust & compact. Available in various sizes, flow rates & connection options, static spray balls can be used for a wide range tank cleaning applications.



Cleaning Efficiency
Class 1

Technical Data

Materials

Stainless steel 316L, PTFE.

Pressure

Design pressure: 1 - 3 bar
Recommended pressure: 2 bar

Spray pattern



360°



180° up



180° down

Design

Self-lubricating with cleaning liquid.

Installation

Functions effectively in every position.

Temperature




Max. temperature: 200°C

Surface finish (Standard)

Exterior: Ra 0.6 µm
Interior: Ra 0.8 µm

Surface finish (Electro-polished)

Exterior: Ra 0.5 µm
Interior: Ra 0.5 µm

Spray Angle	Ordering Code	Flow [l/min] @ Pressure [Bar]			Connection	Spray Ø (m)
		1	2	3		
360° 	7004.36.01.SS.381	91	129	159	1-1/2" Slip-On	2.7
	7004.36.02.SS.381	99	139	172	1-1/2" Slip-On	2.7
	7004.36.03.SS.381	106	149	184	1-1/2" Slip-On	2.8
	7004.36.04.SS.381	113	159	196	1-1/2" Slip-On	2.8
	7004.36.05.SS.381	120	169	209	1-1/2" Slip-On	3.0
	7004.36.06.SS.381	127	179	221	1-1/2" Slip-On	3.1
	7004.36.07.SS.381	134	189	233	1-1/2" Slip-On	3.2
7004.36.08.SS.381	141	199	244	1-1/2" Slip-On	3.2	
180° Up 	7004.18U.01.SS.381	91	129	159	1-1/2" Slip-On	2.7
	7004.18U.02.SS.381	99	139	172	1-1/2" Slip-On	2.7
	7004.18U.03.SS.381	106	149	184	1-1/2" Slip-On	2.8
	7004.18U.04.SS.381	113	159	196	1-1/2" Slip-On	2.8
180° Dn 	7004.18D.01.SS.381	91	129	159	1-1/2" Slip-On	2.7
	7004.18D.02.SS.381	99	139	172	1-1/2" Slip-On	2.7
	7004.18D.03.SS.381	106	149	184	1-1/2" Slip-On	2.8
	7004.18D.04.SS.381	113	159	196	1-1/2" Slip-On	2.8

Pin of stainless steel 316L supplied as standard with slip-on models.

